

QUICKFILL



A high solid content primer/filler

Part N°: 34363 (QFL) - 500ml aerosol

Features

- One part
- High solid content
- Extremely good coat depth with each pass
- Very flexible
- Compatible with most leading automotive paints
- Good adhesion to many surfaces
- Dries fast - 20 minutes

Benefits

- No mixing required
- Fills fast & saves material
- Good fill & build qualities
- Flexes with plastic & metal components
- No comebacks
- No comebacks
- Saves time

Applications

Quickfill has been designed to provide a quick, easy and safe alternative to 2K primer fillers for small, localized repair areas.

It removes the need for the vehicle to be moved to a paint booth for applying small areas of primer to the repaired area, as well as the mixing of minimum amounts of 2K paint and resultant wastage.

It also reduces the amount of solvent intake to a bodyshop as no paint gun cleaner is needed. Quickfill dries in approx. 20 minutes, allowing final flattening to be carried out quickly prior to final painting.

Quickfill has very high adhesion and flexibility, making it ideal for repairs to not only steel panels, but also plastic components such as bumpers and mirrors.

Instructions

1. Shake well before use.
2. Ensure area to be primed/ filled is clean using KENT Acrysol (ABS) or Speedy 500 (ACR).
3. Keeping can 20 - 30 cm away, apply product in light coats as this will enable fast dry times between coats and a build up of total coat depth in a shorter time, also eliminating the trapping of solvent in finished repair which will cause solvent pop.
5. Allow to dry for 20 minutes at room temperature.
6. Sand smooth if required.
7. Can be oversprayed with most standard solvent automotive paints.

DS01

Hints & Tips

To avoid nozzle clogging after use: turn aerosol upside down and spray.



Certificate No. 1427
ISO 9001:2008

QUICKFILL

Technical Information

Part N°:	34363	Resin base:	Acrylic
Description:	Quickfill	Percentage of solids:	17.6%
Shelf Life:	24 months	Operating temp (ideal):	+15° C to +25° C
Selling Unit:	EA	Operating temp (absolute):	+10° C to +30° C
Stock Code:	QFL	Working temp of dry film:	-40° C to +80° C
Customs Tarif Code:	3208 20 90	Theoretical coverage (300 microns):	2.5m ²
SDS:	Yes	Resistance to petrol/diesel:	Excellent
VOC:	630g/L		
Coat Depth:	Light 50, heavy 100 microns		
Dry time:	20 mins approx.		

Associated Products: Body fillers, Acrysol (ABS/SAB), Plastic Repair System, Waterproof and Dry Abrasive Paper

Market Segments

Primary



Secondary



Health & Safety Information



IRRITANT

Contains Xylene, mixed isomers, pure



EXTREMELY INFLAMMABLE

R36 Irritating to eyes. **R52/53** Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. **R66** Repeated exposure may cause skin dryness or cracking. **R67** Vapours may cause drowsiness and dizziness. **S16** Keep away from sources of ignition - No smoking. **S23** Do not breathe vapour/spray. **S26** In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. **S37** Wear suitable gloves. **S51** Use only in well-ventilated areas. **S60** This material and its container must be disposed of as hazardous waste. **WARNING: Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50° C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Contains 3-(isodecylloxy)propylammonium acetate - may cause an allergic reaction.**

Om u in staat te stellen de meest geschikte Persoonlijke Beschermings- en Veiligheidsmiddelen aan te wenden bij het gebruik van onze producten, adviseert KENT u de richtlijnen zoals die op de verpakking van het product vermeld staan, nauwkeurig op te volgen. De richtlijnen staan er voor uw veiligheid en KENT levert een assortiment Persoonlijke Beschermings- en Veiligheidsmiddelen zoals kleding, brillen, gelaatsschermen en maskers conform de meest recente Europese voorschriften. Heeft u behoefte aan aanvullend advies, neem dan contact met ons op zodat wij u daarbij kunnen assisteren. Telefoon: BE +32 10 48 76 40 - NL +31 85 4868360

Voorwaarden

Niets uit deze uitgave mag worden veeleenvoudig en/of openbaar gemaakt door middel van druk, fotokopie, microfilm of welke andere wijze dan ook zonder voorafgaande schriftelijke toestemming van KENT Belux sprl/bvba of KENT Nederland B.V.

KENT Belux sprl/bvba stelt deze publicatie met de grootst mogelijke zorg samen maar kan geen aansprakelijkheid aanvaarden voor eventuele schade die zou kunnen voortvloeien uit enige fout die in deze uitgave zou kunnen voorkomen door onnauwkeurigheden of nalatigheden in de informatie of voor schade ten gevolge van of in verband met het gebruik van deze informatie. KENT Belux sprl/bvba en Kent Nederland B.V. handelen onder de naam KENT.

Vestigingsadres:

KENT Belux sprl/bvba

Rue Emile Francqui, 4

1435 Mont-Saint-Guibert

BTW: BE 0414.239.587

KENT Nederland B.V.

Minervum 7444-G - 4817 ZG Breda.

BTW : NL 8172.47.658.B01

KENT Belux sprl/bvba : Rue Emile Francqui, 4 – 1435 Mont-Saint-Guibert
Tel: +32 10 48 76 40 Fax: +32 10 24 34 53 www.kent-europe.com

KENT Nederland B.V. Minervum 7444-G - 4817 ZG Breda
•Tel: +31 85-4868360 - Fax: + 31 85-4868369